



**Georgia-Pacific**  
Chemicals

# GP<sup>®</sup> 7565LF Crosslinking Resin

## PRODUCT INFORMATION

### INTRODUCTION

GP<sup>®</sup> 7565LF is a low-color, heat-reactive phenolic resin solution in n-butanol used as a crosslinker for hydroxyl-containing polymers such as epoxies, polyesters, vinyls and acrylics. It can be emulsified into water-based epoxy resins and is designed to maximize chemical resistance.

### APPLICATIONS

GP 7565LF resin is used primarily as a protective coating for cans, drums and pails, pipes and other metal protection purposes. It is used where light colored coatings are required.

### STORAGE AND HANDLING

GP 7565LF resin is a heat-reactive resin with a limited shelf life. It is shipped in drums. It is suggested that the resin be stored in a dry location at or below 60°F (15°C) in order to maximize storage life. Actual storage life will be determined by your specific formulation. This product should be stored and used in a well-ventilated area.

The proper personal protective equipment should be worn whenever GP 7565LF resin is used or handled. For safety and health information, please refer to the Safety Data Sheet for GP 7565LF resin available from Georgia-Pacific Chemicals.

### TYPICAL PROPERTIES

Appearance	Liquid, Solution in n-Butanol
Viscosity @ 25°C, cP (mPa*sec)	2500 - 4000
Solids, wt. %	68 -72
Specific Gravity @ 25°C	Approximately 1.08

**866-4GP-CHEM**

GPChemical@gapac.com  
www.gp-chemicals.com