



Georgia-Pacific
Chemicals

GP[®] BKS-2600 Coating Resin

PRODUCT INFORMATION

INTRODUCTION

GP[®] BKS-2600 heat-reactive phenolic resin solution in ethanol is formulated to provide chemical resistance for protective coatings for rigid metallic substrates.

APPLICATIONS

GP BKS-2600 resin is used primarily in applications such as drums and pails, pipes, tanks and railcars.

CERTIFICATIONS

GP BKS-2600 coating resin is compliant with the U.S. Food and Drug Administration (FDA) according to Title 21 CFR §175.105, §175.300, §176.180, §177.1210 and, §176.170 as resinous and polymeric coatings.

STORAGE AND HANDLING

It is recommended that heat-reactive GP BKS-2600 resin be stored in a dry place at temperatures at or below 50°F (10°C) to optimize shelf life. Storage in sunlight should be avoided. Storage life is dependent on your product's formulation using GP BKS-2600 resin. This product should be stored and used in areas with good ventilation.

The proper personal protective equipment should be worn whenever GP BKS-2600 resin is used or handled. For safety and health information, please refer to the Safety Data Sheet available from Georgia-Pacific Chemicals.

TYPICAL PROPERTIES

Form	Solution in ethanol
Viscosity @ 25°C, cP (mPa*sec)	700 – 1000
Solids, wt. %	52 – 56
Specific Gravity @ 25°C	Approximately 1.04 – 1.07

866-4GP-CHEM

GPChemical@gapac.com
www.gp-chemicals.com