



**Georgia-Pacific**  
Chemicals

# GP<sup>®</sup> CK-2400 Coating Resin

## PRODUCT INFORMATION

### INTRODUCTION

GP<sup>®</sup> CK-2400 coating resin is a novolac resin modifier for alkyd and epoxy air dry coatings designed to improve water resistance, hardness, leveling, gloss and intercoat adhesion.

### APPLICATIONS

GP CK-2400 resin is used in cold blend and protective coatings for metal protection in marine and maintenance applications.

### STORAGE AND HANDLING

Typically shipped in bags, GP CK-2400 novolac resins are non heat-reactive and should be stored in a dry location at temperatures at or below 60°F (16°C). Storage in sunlight should be avoided. Resin storage life under the recommended conditions is two years, possibly longer dependent on your product's formulation using GP CK-2400 resin. This product should be stored and used in areas with good ventilation.

The proper personal protective equipment should be worn whenever GP CK-2400 resin is used or handled. For safety and health information, please refer to the Safety Data Sheet for GP CK-2400 resin available from Georgia-Pacific Chemicals.

### TYPICAL PROPERTIES

Appearance	Solid, flake
Softening Point, °F (°C)	290 – 315 (143 – 157)
Gardener (50:50 in xylene)	8 maximum

**866-4GP-CHEM**

GPChemical@gapac.com  
www.gp-chemicals.com